

NEW

 Compatible

CV18DA

Cordless Multitool

18V - OIS

OIS And Starlock compatible

3.6° oscillation angle

Low vibration and noise



Specifications

Voltage	18V
No-load oscillation frequency	6,000 - 20,000 /min.
Oscillating angle	3.6°
Accessory system	OIS ¹
Brushless motor	✓
Variable speed	✓
Toolless accessory change	✓
Soft start	✓
Constant speed control	✓
Dimensions (L x H)	327 x 87 mm
Weight ²	1.6 kg

Characteristics

- Updated locking mechanism for a fast toolless change of accessories
- Wide range of optional HIKOKI accessories available
- Low vibration and noise for high user comfort
- Wide 3.6° oscillation angle for fast and powerful cuts
- Variable speed regulation for the right speed for each application
- Non-snapping very smooth closing accessory locking lever for safe change of accessories
- Brushless motor for high power, less wear and a long service life

Versions³

CV18DAWRZ: 000000000000	2x BSL1820M, 1x charger UC18YSFL, cutting blade wood/metal, sanding pad, 10x sanding paper (P80, P120), stackable case HSC II
CV18DAW2Z: 000000000000	Cutting blade wood/metal, sanding pad, 10x sanding paper (P80, P120), stackable case HSC II
CV18DAW3Z: 000000000000	Cutting blade wood/metal, stackable case HSC II
CV18DAW4Z: 000000000000	Cutting blade wood/metal, cardboard box

Change the barcode placeholder 000000000000 into the specific one for the version that is shown

Change the URLs accordingly

¹ Starlock compatible.

² Weight according to EPTA-2004 procedure.

³ Standard accessories vary by country or area.

Read everything about our services at hikoki-powertools.eu

