

DV18DCJRZ

Cordless Impact Driver Drill

18V

4966376405190

NEW

Industry's top class power - 140 Nm

Robust aluminium gear housing

Reactive Force Control with Gyro sensor



Compatible with

BRUSHLESS
RFC

Specifications

Voltage		18V
Max. capacity drilling	Wood	102 mm
	Metal	16 mm
	Brick	20 mm
Max. capacity screwing	Wood screw	12 x 100 mm
	Machine screw	6 mm
Capacity drill chuck		13 mm
Max. torque	Hard joint	140 Nm
	Soft joint	70 Nm
No-load speed	Low mode	0 - 500 /min.
	High mode	0 - 2,000 /min.
No-load impact rate	Low mode	0 - 7,500 /min.
	High mode	0 - 30,000 /min.
Slip torque	Stages	22
	Torque	1.5 to 8.0 Nm
Motor type		Brushless
Anti-kickback function (RFC with Gyro sensor)		Yes
Dimensions L x H x W		190 x 267 x 70 mm
Weight ¹	With BSL36A18	2.8 kg
	Without battery	2.1 kg

Characteristics

- Industry's top class power and drilling speed for toughest applications
- Improved airflow design and heat sink keep electronics cool
- Robust aluminium gear housing provides additional rigidity
- RFC technology and a Gyro sensor detect overburdening of the tool bit and stop the motor to reduce twisting of the main unit
- Compact body to work in tight and hard to reach spaces
- Constant speed control provides additional power so that the motor can maintain its speed under load
- Metal chuck with carbide inserts for highest gripping force
- Rotatable side handle provides ease of use and simplicity of operation
- Ergonomic soft grip handle for optimal control and longer comfortable working

Versions²

DV18DCJRZ: 2x battery BSL36A18, charger UC18YSL3, stackable case HSC II

DV18DCW2Z: Stackable case HSC II

¹ Weight according to EPTA-2004 procedure.

² Standard accessories vary by country or area.

Read everything
about our services at
hikoki-powertools.com

